



The enhanced ShockLog RD298 combines Lamerholm Electronics advanced tri-axel piezo electric accelerometer technology with sophisticated electronics and software to offer an advanced shock and vibration monitoring instrumentation.

The 298 has been designed to monitor shock and vibration based on acceleration or velocity measurements. The device has several unique features, which make it suitable for application where the cost of exposure to out of specification environmental influences is very high. The instrument is equally suitable for protecting high value fixed or mobile installations and investigating shock and vibration during transportation.

The comprehensive Windows based software programme allows you to programme your own wake up, warning and alarm levels and frequency of data collection as well as the setting of the Acceleration or Velocity range and Frequency filter. When a programmed impact level is exceeded a visual alarm will alert you as well as storing the data for future analysis.

Features:

- ° Built in temperature sensor with optional humidity sensors
- ° Three built in accelerometers
- ° Completely self contained (battery operated)
- ° Velocity or acceleration measurements
- ° Adjustable Warning and alarm thresholds
- ° User selected frequency cut off
- ° Low cost standard AA size lithium or alkaline
- ° LED operation, warning and alarm status indicators
- ° Date and time stamping
- ° RF screened and CE certified battery
- ° Greater than 18 month battery life
- ° Complete journey profile
- ° Detailed record significant events
- ° Optional external sensors
- ° Tamper-proof factory and user passwords
- ° Data stored in non volatile memory

The ShockLog is the ability to set alarm conditions on any the selected slot data; most parameters have a high and low alarm setting point.

ShockLog

Product Code	29800STF0 29800STF0K 29800ETF0 29800ETF0K
Series	ShockLog

Instrument

Dimensions:	123 x 78 x 55mm
Weight:	500grams
Power Supply:	2 x 3.6V Lithium thionyl chloride 2 x 1.5V Alkaline size AA
Case Material:	Aluminium
Operating Temperature Range:	Accuracy (full range) -2 to +2°C Extended range -40 to +85°C
Humidity:	-3 to +3% RH
Scale Factor:	± 2%
Acceleration Ranges:	1, 3, 10, 30, 100 & 200g
Velocity Ranges:	1, 3, 10, 30, 100 & 200cm/s
Warning & Alarm Thresholds (%):	5 to 95% (% of range)
Dynamic Range:	2.5mg to 100g

Accessories

Code	29900: HPT (humidity, pressure & temperature) 1bar 29900B2: HPT (humidity, pressure & temperature) 2 bar 29835: RD298 RS232 3m communication cable 65014: RD298 USB adaptor cable 29800RA: RD400 single axis accelerometer 40400: RD404 tilt & Roll accelerometer 40100A: RD401A RIU battery powered remote indicator unit
-------------	--

Benefits:

- ° Provides a visible deterrent to incorrect operation and handling
- ° Decreases costs related to damage incurred during operation, shipping, handling and storage
- ° Highlights potential areas for improvement in operational, shipping and handling processes
- ° Isolates when and where unacceptable conditions occur and identifies accountable parties
- ° Confirms acceptable conditions during operation, shipping, handling and storage
- ° Operational and journey profiling
- ° Alerts recipient to potential damage upon arrival and, therefore, inspection require