

CASES
1300
Case



1300 Case

- Watertight, crushproof, and dustproof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1300 Case Configurations

Cat. #	Description
1300	1300 Case
1300NF	1300 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1300 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)		9.17" x 7.00" x 6.12" (23.3 x 17.8 x 15.5 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.18" (3 cm)	4.93" (12.5 cm)	6.11" (15.5 cm)	
Interior Cubic Volume			
0.23 cubic feet (6.44 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
3.53 lbs. (1.6 kg)	3.09 lbs. (1.4 kg)	12.35 lbs. (5.6 kg)	
Range Temperature			
-40 / 210° F (-40 / 99° C)			

1300 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1300 Case Accessories

Cat. #	Description
1200PF	Special Application Panel Frame
1203	Replacement O-ring
1301	4 pc. Replacement Foam Set

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com