

CASES
1400 Case



1400 Case

- Watertight, crushproof, and dustproof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1400 Case Configurations

Cat. #	Description
1400	1400 Case
1400NF	1400 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1400 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)		11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.18" (3 cm)	4.00" (10.2 cm)	5.18" (13.2 cm)	
Interior Cubic Volume			
0.31 cubic feet (8.89 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
4.41 lbs. (2 kg)	3.97 lbs. (1.8 kg)	20.06 lbs. (9.1 kg)	
Range Temperature			
-40 / 210° F (-40 / 99° C)			

Personalized Nameplate Available

1400 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1400 Case Accessories

Cat. #	Description
1400PF	Special Application Panel Frame
1401	3 pc. Replacement Foam Set
1403	Replacement O-ring

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com