

CASES
1560
Case



1560 Case

- Retractable extension handle
- Strong polyurethane wheels with stainless steel bearings
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- Watertight, crushproof, and dustproof

1560 Case Configurations

Cat. #	Description
1560	1560 Case
1564	1560 Case with Padded Dividers
1560LOC	1560LOC Laptop Overnight Case
1560NF	1560 Case (No foam)
1560LFC	1560LFC Case (1560LOC with foam in the base)
1560SC	1560SC Studio Case (1560LOC with Padded Dividers)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1560 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
22.07" x 17.92" x 10.42" (56 x 45.5 x 26.5 cm)		19.92" x 14.98" x 9.00" (50.6 x 38 x 22.9 cm)	
Lid Depth	Bottom Depth	Total Depth	
2.00" (5.1 cm)	7.00" (17.8 cm)	9.00" (22.9 cm)	
Interior Cubic Volume			
1.55 cubic feet (44.01 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	

20 lbs. (9.07 kg)

17 lbs. (7.71 kg)

115 lbs.
(52.16 kg)

Range Temperature	No. of Wheels	Retractable Handle
-40 / 210° F (-40 / 99° C)	2	Yes

Personalized Nameplate Available

1560 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1560 Case Accessories

Cat. #	Description
0343	Replacement O-ring
1561	4 pc. Replacement Foam Set
1562	Pick N Pluck™ Sections Only (set of 2)
1565	Padded Divider Set Only
1569	Lid Organizer for 1560 Case

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com