

Uncontrolled document as of September 20, 2015. Refer to website for up to date specifications.

**CASES**  
**1700**  
Long Case



**1700 Long Case**

- Watertight, crushproof, and dustproof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down side handle
- Strong polyurethane wheels with stainless steel bearings
- Stainless steel hardware and padlock protectors
- 3-piece foam set
- Lifetime Guarantee of Excellence

**1700 Long Case Configurations**

Cat. #	Description
1700	1700 Long Case
1700NF	1700 Long Case (No foam)



Black



OD Green\*



Desert Tan

\*OD Green available upon request (minimum quantities apply)

**1700 Long Case Specifications**

<b>Exterior Dimensions (L x W x D)</b>		<b>Interior Dimensions (L x W x D)</b>	
38.12" x 16.00" x 6.12" (96.8 x 40.6 x 15.5 cm)		35.75" x 13.50" x 5.25" (90.8 x 34.3 x 13.3 cm)	
<b>Lid Depth</b>	<b>Bottom Depth</b>	<b>Total Depth</b>	
1.75" (4.4 cm)	3.50" (8.9 cm)	5.25" (13.3 cm)	
<b>Interior Cubic Volume</b>			
1.47 cubic feet (41.52 cubic decimeter)			
<b>Weight with foam</b>	<b>Weight without foam</b>	<b>Buoyancy Max.</b>	
16.98 lbs. (7.7 kg)	16.09 lbs. (7.3 kg)	136.91 lbs. (62.1 kg)	
<b>Range Temperature</b>	<b>No. of Wheels</b>		
-40 / 210° F (-40 / 99° C)	2		

## 1700 Long Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150j • Def Stan 81-41/STANAG 4280

## 1700 Long Case Accessories

Cat. #	Description
1701	3 pc. Replacement Foam Set
1703	Replacement O-ring

### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [CSR.Consumer@pelican.com](mailto:CSR.Consumer@pelican.com) • [www.pelican.com](http://www.pelican.com)