

CASES

1450
Case



1450 Case

- Watertight, crushproof, and dustproof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1450 Case Configurations

Cat. #	Description
1450	1450 Case
1454	1450 Case with Padded Dividers
1450NF	1450 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request (minimum quantities apply)

1450 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
16.54" x 13.03" x 6.84" (42 x 33.1 x 17.4 cm)		14.66" x 10.24" x 6.12" (37.2 x 26 x 15.5 cm)	
Lid Depth	Bottom Depth	Total Depth	
1.75" (4.4 cm)	4.37" (11.1 cm)	6.12" (15.5 cm)	
Interior Cubic Volume			
0.53 cubic feet (15.06 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
6.39 lbs. (2.9 kg)	5.51 lbs. (2.5 kg)	30 lbs. (13.61 kg)	
Range Temperature			
-40 / 210° F (-40 / 99° C)			

Personalized Nameplate Available

1450 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280

1450 Case Accessories

Cat. #	Description
1450PF	Special Application Panel Frame
1451	3 pc. Replacement Foam Set
1453	Replacement O-ring
1455	Padded Divider Set Only

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com